

## PRODUCT AND SERVICE BENEFITS

Countrywide network of branches and agencies.

❖ A comprehensive product warranty.

Maintenance Free Factory Sealed Never Add Water

## **SALIENT DESIGN FEATURES**

LONG FLOAT LIFE Calcium alloy grids and plates to minimise corrosion.

Envelope separators to eliminate internal short circuits.

High density active material formulation. HIGH CYCLING DESIGN

Glass matt backed separators for active material retention.

❖ EXCEPTIONAL HIGH RATE

PERFORMANCE

Oversized internal inter-cell connector cross section. ENHANCED SAFETY

Central venting system.

Flashback arrestor.

High impact strength container.

Built in State of Charge Indicator EASY TO MAINTAIN

Locally manufactured

CONSTANT POWER DISCHARGE DATA DOWN TO 10.2V (1.7) AT 25°C (WATTS PER CELL)								
Туре	10 Min	15 Min	20 Min	25 Min	30 Min	45 Min	60 Min	
FMF102	341	264	213	187	166	141	113	
FMF 230	784.3	607.2	489.9	430	381.8	324.30	259.9	

CONSTANT CURRENT DISCHARGE DATA DOWN TO 10.2V (1.7) AT 25°C (AMPS)								
Туре	1 Hour	2 Hour	3 Hour	4 Hour	5 Hour	8 Hour	10 Hour	
FMF 102	58.9	35	25.1	20.7	16.3	12	9.18	
FMF 230	135.5	80.5	57.7	47.6	37.5	27.6	22.52	

## **RANGE TABLE:**

FMF 230 does not have a magic eye.

	Capacity at 20 Hr	Mass					
Туре			Length	Width	Height	Height Incl. Terminal	Terminal
FMF 102	102	26.5	328	171	219	239	Stud
FMF 230	230	60.5	517	276	217	240	Lug

**Corner Liverpool & Bristol Roads,** Benoni South, 1502 P.O. Box 5015 Benoni South, 1502 **South Africa** 

Telephone: +27 11 741 3600 Fax: +27 11 421 2642

In the interests of continuing advancement we reserve the right to modify specifications without prior notice. Copyright subsists in this work. Any unauthorised reproduction, adaption and copying of this document are acts of copyright infringements and entitles First National Battery to take action.



For More Information Contact: **FIRST NATIONAL BATTERY TOLL FREE: 0800 112600** www.battery.co.za

Excis: December 2016